

INTRODUCTION

PISTONS

TSC offers a full range of mud pump pistons for both triplex and duplex pumps. They are:

- Bonded urethane pistons.
- Bonded rubber pistons.
- Replaceable rubber pistons.
- Endurance Premium Bonded Piston.



BONDED URETHANE PISTON

These pistons are constructed of double durometer urethane, bonded to a solid metal hub. Double durometer urethane is designed to provide optimum performance in oil-based mud and high drilling pressures.

Features

- Rated for all drilling operations.
- Maximum operating temperature is 180 °F.
- High pressure mud pump service.
- Extended service life.



INTRODUCTION

N'DURALL PREMIUM BONDED PISTON

TSC's "N'durall" mud pump piston improves drilling contractor economics through advances in technology, improved process control and increased drilling penetration rates.

Chemistry

Manufactured from advanced polymer compounds, the advances in chemistry ultimately provide superior mechanical values and chemical resistance. The increased mechanical values provide resistance to reciprocating pump pistons biggest enemies listed below.

- Heat.
- Abrasion.
- Extrusion.

The advanced polymer compound provides strength to withstand chemical attack from additives used in today's oil, synthetic and water based drilling fluids. The compound also has improved abrasion resistance from drilling solids suspended in drilling muds and excels in high temperature performance capable of operating in fluid temperature up to 300°F.

Improved Process Control

The "N'durall" carries stamped batch numbers on the piston body for use in monitoring manufacturing dates and as an aid in rotating shelf stock.

Design

The single durometer design and open mold casting contribute to overall performance and improved economics.

Machining

CNC machining of steel piston heads yields close tolerances for improved performance.

Applications

- High Pressure Drilling.
- Elevated Mud Temperature.
- Synthetic Drilling Fluid.
- Ceramic and Zirconia Liners.
- Chrome Sleeved Liners.



INTRODUCTION

BONDED RUBBER PISTON

TSC pistons are constructed of nitrile rubber bonded to a solid metal hub. The oil resistant rubber is designed to provide optimum performance in oil base or water base mud and high drilling pressures.

Features

- High tensile strength.
- Rated for all drilling operations.
- Maximum operating temperature is 250°F.
- Extended service life.



REPLACEABLE RUBBER PISTON

TSC replaceable rubber pistons are made with nitrile rubber to resist extrusion and abrasion. These pistons are fully interchangeable with most other manufactures products. Available sizes range from 3" through 7-1/2" and series are A, B, K and L.

Features

- High tensile strength.
- Rated for all drilling operations.
- Maximum operating temperature is 250°F.
- Extended service life.



FLUID END EXPENDABLES

GARDNER DENVER

PZ-8

7 x 8

LINERS		ZIRCONIA LINERS	LINER GASKETS	PISTONS				PISTON RUBBER
SIZE	PART NUMBER	PART NUMBER	PART NUMBER	URETHANE BONDED	RUBBER BONDED	N'DURALL BONDED	REPLACEABLE RUBBER	PART NUMBER
4"	TS-1191-40HP	TS-07493400	G-692 *	LLU-40-K15	LL-40-K15	HPW-40-K15	I-40-K15	TM-40-KR
4 1/2"	TS-1191-44HP	TS-07493450	G-692 *	LLU-44-B15	LL-44-B15	HPW-44-B15	I-44-B15	TM-44-BR
5"	TS-1191-50HP	TS-07493500	G-692 *	LLU-50-B15	LL-50-B15	HPW-50-B15	I-50-B15	TM-50-BR
5 1/2"	TS-1191-54HP	TS-07493550	G-692 *	LLU-54-B15	LL-54-B15	HPW-54-B15	I-54-B15	TM-54-BR
5 3/4"	TS-1191-56HP	TS-07493575	G-692 *	LLU-56-B15	LL-56-B15	HPW-56-B15	I-56-B15	TM-56-BR
6"	TS-1191-60HP	TS-07493600	G-692 *	LLU-60-B15	LL-60-B15	HPW-60-B15	I-60-B15	TM-60-BR
6 1/4"	TS-1191-62HP	TS-07493625	G-692 *	LLU-62-L15	LL-62-L15	HPW-62-L15	I-62-L15	TM-62-LR
6 1/2"	TS-1191-64HP	TS-07493650	G-692 *	LLU-64-L15	LL-64-L15	HPW-64-L15	I-64-L15	TM-64-LR
6 3/4"	TS-1191-66HP	TS-07493675	G-692 *	LLU-66-L15	LL-66-L15	HPW-66-L15	I-66-L15	TM-66-LR
7"	TS-1191-70Cr		G-692 *	LLU-70-L15	LL-70-L15	HPW-70-L15	I-70-L15	TM-70-LR
VALVES, SEATS, SPRINGS						GASKETS		
	4 WEB DESIGN	3 WEB DESIGN	FULL OPEN (1)	FULL OPEN (2)		PART NUMBER		
VALVE	TS-7-EEF	TS-202PZL482A	TS-0985M	TS-7-V1	VALVE COVER GASKET	G-749 *		
SEAT	TS-7-DDB1	TS-202PZL039	TS-1370M	TS-7-S1	CYLINDER HEAD GASKET	G-749 *		
SPRING	TS-5710-115	TS-78H44	TS-0702M	TS-5710-115L	WEAR PLATE GASKET	G-758*		
INSERT (Urethane)	TS-7-WI	TS-201PZL106	TS-7-MI	TS-7-FI	EXTENSION ROD SEAL	TS-2011872-2		
INSERT (Rubber)	TS-7-WR	TS-202PZL106	-	-	EXTENSION ROD BAFFLE	TS-PZ840		
PISTON ROD & EXTENSION ROD								
ROD CLAMP	PISTON ROD STUD	PISTON NUT	THREADED TYPE PISTON ROD	CLAMP TYPE PISTON ROD	SUB ROD	THREADED TYPE EXTENSION ROD	CLAMP TYPE EXTENSION ROD	
TMPZ9-03-08	N/A	TM-NUT	TM-202	TM-191	N/A	TMPZ7-01-06T	TMPZ8-01-06	
FLUID END MODULE								
FLUID END MODULE STUDED			MODULE SEAL SET			STUDS & NUTS SET		
TS-205PZL029D			TMPZ9-SEALKIT			TMPZ9-STUDSET		

TSC does not warrant or represent that any of such information is accurate, or that any products listed are compatible with each other. Any deviations from the OEM products should be verified as to compatibility.

TSC Manufacturing and Supply LLC, 13788 West Road, Suite 100, Houston, Texas 77041, USA
 Tel: +1 832 456 3900 Fax: +1 832 456 3998 E-mail: sales@t-s-c.com

