
Mud Agitator

The TSC Mud Agitator is an important part of the solids control system. It is mounted on the circulating tank so that the agitator vanes engage the mud by stirring it uniformly. The TSC design features rigid shafts which are offered in variable lengths to fit different pit dimensions.

Please contact your local TSC representative to learn more about the complete line of TSC solids control products.



Model	HA-5.5	HA-7.5	HA-11	HA-15
Power	7.4 HP	10 HP	14.8 HP	20 HP
Motor speed (rpm)	1,440/1,750	1,440/1,750	1,440/1,750	1,440/1,750
Impeller speed (rpm)	58/70	58/70	58/70	58/70
Impeller diameter (in)	23.62/19.68	31.5/25.59	35.43/29.52	39.37/31.5
Weight	1,168 lbs	1,323 lbs	1,440 lbs	1,830 lbs
Dimensions	41×30×24.4	46×30×26	51×32×28	53×32×28

Model	HA-2.2	HA-4	HA-18.5	
Power	3 HP	5.4 HP	25 HP	
Motor speed (rpm)	1,440/1,750	1,440/1,750	1,440/1,750	
Impeller speed (rpm)	58/70	58/70	58/70	
Impeller diameter (in)	15.75/13.78	19.69/15.75	47.25/39.37	
Weight	331 lbs	1,052 lbs	2,213 lbs	
Dimensions	26×20×18	37×28×22	61×36×30	



TSC Manufacturing and Supply LLC, 13788 West Road, Suite 100, Houston, Texas 77041, USA Tel: +1 832 456 3900 Fax: +1 832 456 3998 Email: sales@t-s-c.com Visit our Website at www.t-s-c.com